


Overview

HPE MSA 2062 Storage Array

Looking for seriously simple and affordable flash storage? The HPE MSA 2062 Storage is a flash-enabled system designed for affordable application acceleration for small and remote office deployments. Don't let the low cost fool you. The MSA 2062 gives you the combination of simplicity, flexibility and advanced features you many not expect in an entry-priced storage array. Starting with 3.84 TB of embedded flash capacity, you can scale the system from there with any combination of solid state disks (SSD), high-performance Enterprise SAS HDDs, or lower-cost Midline SAS HDDs. Capable of delivering in excess of 325,000 IOPS, the MSA 2062 saves you up to 32% with an all-inclusive software suite and 3.84-TB of flash capacity included. It's seriously simple and affordable flash storage to help you achieve high performance yet meet challenging budgets.



HPE MSA 2062 Storage



HPE MSA 2062 Storage

| Item | Description |
|------|---|
| 1. | Power Switch |
| 2. | Redundant Power and Cooling Module (AC or DC) |
| 3. | Host connection ports (16Gb FC, 10GbE iSCSI or 12Gb SAS depending on model) |
| 4. | Ethernet management port |
| 5. | 12Gb SAS expansion port |
| 6. | Controller A (Inverted) |
| 7. | Controller B |

Overview

What's New

- MSA 2062 LFF and SFF array models supporting 10GBase-T host connectivity. Each controller includes four (4) integrated RJ45 Ethernet (copper) ports for connection to switch or server using CAT6/7 cabling – no SFPs required. Results in infrastructure savings of up to 62% when deploying iSCSI storage configurations.
- IN110Rxxx firmware update supporting up to 34% greater random read performance (IOPs) for 2060 and 2062 array models. Firmware update available via the MSA firmware page and the MSA Health Check tool for all MSA Gen6 array models.
- HPE MSA 18TB SAS 7.2K LFF HDD available in single drive and six-pack bundles options.

MSA 2062 Storage Models

| Description | SKU |
|---|--------|
| HPE MSA 2062 16Gb Fibre Channel LFF Storage | R0Q79A |
| HPE MSA 2062 16Gb Fibre Channel SFF Storage | R0Q80A |
| HPE MSA 2062 10GbE iSCSI LFF Storage | R0Q81A |
| HPE MSA 2062 10GbE iSCSI SFF Storage | R0Q82A |
| HPE MSA 2062 12Gb SAS LFF Storage | R0Q83A |
| HPE MSA 2062 12Gb SAS SFF Storage | R0Q84A |
| HPE MSA 2062 10GBASE-T iSCSI LFF Storage | R7J70A |
| HPE MSA 2062 10GBASE-T iSCSI SFF Storage | R7J71A |

Notes:

- Includes an MSA 2060-branded LFF or SFF array chassis depending on model, two MSA 2060 controllers, two 1.92TB Read Intensive SSDs, One Advanced Data Services LTU (preinstalled on the array), two AC power supplies, two 1.5m PDU cords (IEC C14), one rack-mount kit.
- SFPs are not included in the base Storage Systems.
- All MSA 2062 Fibre Channel and 10GbE iSCSI array models must use the appropriate Gen6 SFP option – please review “Configuration Information” section for further details.



Standard Features

HPE MSA 2062 Storage

Array

| | |
|---------------------------------|---------------------|
| Access Type | Block |
| Form Factor | 2U, SFF or LFF |
| Number of controllers per array | 2 |
| Number of host ports per array | 8 |
| FC host connectivity | 16Gb |
| iSCSI host connectivity | 10GbE and 10GBase-T |
| SAS host connectivity | 12Gb |

Cache, per array

| | |
|---|---|
| Max Read cache per array | 8TB |
| Data (read/write) cache + system memory per array | 24GB |
| Pool Capacity | Two Pools with 1 PB each |
| RAID Levels supported: | RAID 0*, 1, 5, 6, 10, MSA-DP+ Notes: *Read Cache Only |

Enclosures

| | |
|--|----------------|
| Expansion Drive Enclosures | 0-9 enclosures |
| LFF/SFF array/enclosure mixing | Supported |
| Maximum number of drives per array enclosure | 24 SFF/12 LFF |
| Maximum number of drives per drive enclosure | 24 SFF/12 LFF |
| Drive enclosure interface type | 12Gb SAS |

Drives

| | |
|--------------------------------------|------------------------------|
| Maximum total HDDs per array | 240 SFF / 120 LFF |
| Maximum total SSDs per array | 240 SFF / 120 LFF |
| Max raw capacity per array enclosure | 88.32TB SFF / 183.84TB LFF |
| Max raw capacity per drive enclosure | 92.16TB SFF / 216TB LFF |
| Max raw capacity per array | 917.76TB SFF / 2127.84TB LFF |

Drive Capacities

| | |
|----------|---|
| SFF SSDs | 960GB, 1.92TB, 3.84TB |
| LFF SSD | 1.92TB |
| SFF HDDs | 15K: 900GB 10K: 600GB, 1.2TB, 1.8TB, 2.4TB |
| LFF HDDs | 7.2K: 6TB, 8TB, 10TB, 12TB, 14TB, 16TB, 18TB |

Software Features

| | |
|-----------------------------|---|
| Thin Technologies | Thin Provisioning, Space Reclamation, Thin Rebuild |
| Tiering | Performance Tier, Standard Tier, Archive Tier |
| Replication | Snapshots (512), Volume Copy, Remote Snaps |
| Quality of Service | Virtual Tier Affinity |
| Bundled/Integrated Licenses | Advanced Data Services LTU standard on MSA 2062 (preinstalled on the array) |



Standard Features

Additional Features

| | |
|------------------------------|------|
| Maximum number of volumes | 512 |
| Maximum number of snapshots | 512 |
| Maximum number of hosts | 512 |
| Maximum number of initiators | 1024 |
| Customer self-installable | Yes |
| Customer self-repairable | Yes |
| Customer self-upgradeable | Yes |
| Health Check analytics | Yes |
| Energy Star Certified | Yes |

All MSA 2062 models offer a common set of valuable features

MSA 2062 Solution

- MSA 2060-branded LFF or SFF array chassis depending on model
- Two AC power supplies
- Two MSA 2060 Storage Controllers (FC, iSCSI or SAS)
- Two 1.92TB Read Intensive SSDs
- One Advanced Data Services LTU (preinstalled on the array)

Chassis

- 12 drive bay LFF or 24 drive bay SFF 2U base arrays, depending on model
- 12 drive bay LFF or 24 drive bay SFF 2U expansion enclosures, depending on model
- 12Gb SAS disk expansion protocol
- New next-generation drive carriers
- New optional locking bezel

Storage Controllers

- Dual hot-swappable active/active controllers
- 4 host ports per controller, 8 host ports per array
- 16Gb Fibre Channel, 10GbE iSCSI, 10GBase-T iSCSI, and 12Gb SAS protocol support
- Auto negotiation
- New next-generation RAID offload ASIC and Processor
- 24GB system cache
- 12Gb SAS expansion ports
- Battery-free cache backup with super capacitors and compact flash

Expansion Capacity

- Maximum expansion of 9 drive enclosures (either LFF and/or SFF)
- Maximum of 240 SFF or 120 LFF drives
- Maximum of 921.6TB SFF / 2.16PB LFF raw capacity



Standard Features

Storage Services

- Virtual Storage
 - Up to two pools (1PB each)
 - Automated tiering v2.0
 - SSD read cache extension
 - Thin Provisioning
 - Volume Copy
 - Snapshot capability (512 snapshots per array, standard)
- Virtual Storage Disk Groups can be spanned across multiple enclosures.
- Virtual Storage RAID levels supported: 1, 5, 6, 10, MSA-DP+
- New disk group type (MSA-DP+):
 - Integrated sparing
 - Fast rebuilds
 - Improved sequential performance
 - Incremental disk group expansion

Management

- New redundant web based interface (SMU v4)
- HPE MSA Health Check
- New RESTful interface
- CLI
- Non-disruptive on-line controller code upgrade. Requires Multi-pathing software
- Arxscan Arxview remote monitoring via HPE Complete

Data Protection

- Remote Snapshot (Array-based asynchronous replication, standard)
- VMware Site Recovery Manager
- Zerto Virtual Replication via HPE Complete
- Optional locking bezel

Product Technology

Storage Controllers

- The MSA 2062 FC controllers with 16Gb FC host connectivity.
- The MSA 2062 iSCSI controllers with 10GbE iSCSI host connectivity.
- The MSA 2062 iSCSI controllers with 10GBase-T iSCSI host connectivity.
- The MSA 2062 SAS controllers with 12Gb SAS host connectivity.
- No converged SAN controllers with MSA 2062 models.
- Dual controller active/active (dual pool) design. System can be configured as active/passive (single pool).
- Controllers contain next generation RAID offload ASIC and CPU.
- 24GB System cache
- 12Gb SAS expansion ports.

Notes: The MSA 2062 does not support single controller configurations. Single-controller support is provided only when a controller fails over to its partner controller.



Standard Features

Modular Chassis

- New chassis design with the MSA array and drive enclosures.
- 2U rack height 12 LFF or 24 SFF drive bays, depending on model.
- 12G SAS Midplane.
- Next generation drive modules.

Available Drives

The MSA 2062 Storage Systems support a wide variety of the MSA 3.5-inch LFF drives, and the MSA 2.5-inch SFF drives.

- Solid-State Drives (SSDs) deliver the highest levels of performance and reliability.
 - Enterprise-class SAS hard disk drives (10K/15K RPM) offer a balance of performance, capacity, and cost while delivering enterprise grade reliability.
 - Midline SAS hard disk drives (7.2K RPM) are optimized to provide the best ratio of capacity to cost.
-

Optional Drive Enclosures

MSA 2060 LFF Drive Enclosure

This 2U enclosure is designed to support twelve HPE Storage LFF drives and accepts MSA dual-ported 12Gb SSD, Enterprise SAS and SAS Midline hard drives. The pre-configured MSA 2060 LFF Drive enclosure has two I/O modules and supports the MSA 2060 Storage systems.

- The MSA 2060 LFF Drive Enclosure can be attached to the MSA 2062 LFF or SFF Storage systems.
- Each MSA 2060 LFF Drive Enclosure ships standard with two .5m mini-SAS HD to mini-SAS HD cables for connection to the MSA 2060 array expansion port or existing drive enclosure cascade port.
- LFF and/or SFF drive enclosures can be mixed up to the maximum of nine drive enclosures

HPE MSA 2060 SFF Drive Enclosure

This 2U enclosure is designed to support twenty four HPE Storage SFF drives and accepts MSA dual ported 12Gb SSD, Enterprise SAS, or SAS Midline hard drives. The pre-configured MSA 2060 SFF Drive Enclosure has two I/O modules and supports the MSA 2062Storage systems.

- The MSA 2060 SFF Drive Enclosure can be attached to the MSA 2062 LFF or SFF Storage systems.
 - Each MSA 2060 SFF Drive Enclosure ships standard with a two .5m mini-SAS HD to mini-SAS HD cables for connection to the MSA 2062 array expansion port or existing drive enclosure cascade port.
 - LFF and/or SFF Drive Enclosures can be mixed up to the maximum of nine drive enclosures.
-

Scalability

- LFF configurations can scale up to 216TB per drive enclosure, expandable to 2127.84TB SAS with the addition of a maximum of 9 MSA 2060 LFF Drive Enclosures.
 - SFF configurations can scale up to 92.16TB per drive enclosure, expandable to 917.76TB with the addition of a maximum of nine MSA 2060 SFF Drive Enclosures.
-

Disk Group

A Disk Group is a collection of disks in a given redundancy mode (RAID 1, 5, 6, 10, MSA-DP+). Disk Group RAID level and size can be created based on performance and/or capacity requirements. Multiple Disk Groups can be allocated into a Storage Pool for use with the Virtual Storage features.

LUNs

The MSA 2062 arrays support 512 volumes and up to 512 snapshots in a system. All of these volumes can be mapped to LUNs. Maximum LUN sizes up to 140TB. Thin Provisioning allows the user to create the LUNs independent of the physical storage.



Standard Features

Storage Pools

Storage Pools are comprised of one or more Disk Groups. A volume's data on a given LUN can now span all disk drives in a pool. When capacity is added to a system, users will benefit from the performance of all spindles in that pool.

The MSA 2062 supports large, flexible Volumes with sizes up to 128TiB and facilitates seamless capacity expansion. As pools are expanded data automatically reflows to balance capacity utilization on all drives.

RAID 0, 1, 5, 6, 10, MSA-DP+

The MSA 2062 features several important additional RAID levels. MSA-DP+ offers improved performance, availability, and very fast rebuild times compared to traditional parity RAID by utilizing erasure coding technology. MSA-DP+ includes distributed spare capacity (default is equal to 2x the largest drive), and does not use traditional spare drives. RAID 6 allocates two sets of parity data across drives and allows simultaneous write operations. It can withstand two simultaneous drive failures without downtime or data loss. RAID 10 is mirroring and striping without parity and allows large Disk Groups to be created with high performance and mirroring for fault tolerance. RAID 5 combines the block striping and parity. Because data and parity are striped across all of the disks, no single disk is a bottleneck. Striping also allows users to reconstruct data in case of a disk failure. RAID 0 (Striping) is supported for Read Cache only.

MSA-DP+

MSA-DP+ is a new RAID-based data protection level introduced with the 6th Generation MSA Storage Systems that:

- Maximizes flexibility
- Provides built-in spare capacity
- Optimizes performance due to elimination of idle spares
- Allows for very fast rebuilds, large storage pools, and simplified expansion

If a disk fails in an MSA-DP+ disk group, and the failed disk is replaced with a new disk in the same slot, the replacement disk will be added to the disk group automatically. All disks in an MSA-DP+ disk group must be the same type (Enterprise SAS, for example), but can have different capacities, provided the range of difference does not exceed a factor of two. For example, mixing a 600GB disk and a 1.2TB disk is acceptable; but mixing a 6TB disk and a 16TB disk is not recommended. It is conceivable that a sizeable difference between mixed disk capacities (ratio greater than two) could prevent consuming space on disks due to insufficient distributed space required to support striping.

All disks in an MSA-DP+ disk group are used to hold user data, but not all disks will be used by each page of data. To increase fault tolerance, any available capacity on disks can be allocated as spare for reconstruction purposes. When new data is added, new disks are added, or the system recognizes that data is not distributed across disks in a balanced way, the system moves the data to maintain balance across the disk group. Spare drives are not used by MSA-DP+ disk groups since the RAID design provides built-in spare capacity that is spread across all disks in the disk group. In the case of a disk failure, data will be redistributed to many disks in the disk group, allowing for quick rebuilds and minimal disruption to I/O. The system will automatically default to a target spare capacity that is the sum of the largest two disks in the MSA-DP+ disk group, which is large enough to fully recover fault tolerance after loss of any two disks in the disk group. The actual spare capacity value can change depending on the current available spare capacity in the disk group. Spare capacity is determined by the system as disks are added to a disk group, or when disk groups are created, expanded or rebalanced.

Notes:

- [HPE recommends not mixing disks if the ratio of the largest disk to the smallest disk is greater than two.](#)
- [For more information on MSA-DP+, refer to the HPE MSA 1060/2060/2062 Storage Management Guide.](#)



Standard Features

Configuration and Management Tools

Management access, out-of-band, Storage Management Utility (SMU) V4, CLI.

Interface Types: USB 100/1000 Ethernet.

Protocols Supported SNMP, SMI-S, SSH, SMTP, FTP, SFTP, HTTP, HTTPS, Telnet

Web Browser Support

The MSA 2062 arrays come integrated with a new web browser (SMU v4) and CLI based software for storage and RAID management, setup, configuration, and troubleshooting. The MSA 2062 management supports Microsoft Internet Explorer, Mozilla Firefox, and Google Chrome.

Hot Plug Expansion and Replacement Support

All MSA 2062 models support hot plug expansion and replacement of redundant controllers, drives, fans, power supplies, and I/O modules for simple, fast installation and maintenance. Hot add expansion of drive enclosures is also supported.

HPE Server Compatibility

The MSA 2062 supports most HPE ProLiant, BladeSystems and Integrity servers including

- HPE ProLiant DL, ML Servers
- HPE c-Class Blade Servers
- Integrity servers, IA64
- Compatibility must be confirmed at: <http://www.hpe.com/storage/spock>

Notes: Depends on protocol.

3rd Party Server Support

The MSA 2062 supports most multi-vendor industry standard Intel and AMD based (x86) servers. Hewlett Packard Enterprise requires the Third-Party Server to be logged and listed on the Microsoft Windows Server Catalog.

- Hewlett Packard Enterprise recommends that the Third-Party Server Vendor is an active member of TSANet. Refer to the TSANet website for details: <http://www.tsanet.com>
 - Non-HPE servers will generally be supported if the HPE storage stack is used. This includes supported HPE branded HBAs and drivers, and supported FC switches.
-

OS Support

Refer to the Hewlett Packard Enterprise support statements for complete current OS version support:

<http://www.hpe.com/storage/spock>

- Microsoft Windows Server 2019
- Microsoft Windows Server 2016
- VMware vSphere
- Red Hat Enterprise Linux
- SuSE SLES Linux
- Oracle Linux
- Citrix Hypervisor
- HP-UX

Notes: depends on protocol.



Standard Features

Advanced Data Services Suite

The HPE MSA Advanced Data Services Suite is included and preinstalled as a standard feature on the MSA 2062 at no extra charge.

The standard Advanced Data Services Suite includes the following functionality:

- Performance Tiering
 - 512 Snapshots and Volume Copy
 - Remote Snap functionality
-

Performance Tiering and Archive Tiering

Disk tiers are comprised of aggregating 1 or more Disk Groups of similar physical disks. The MSA 2062 supports 3 distinct tiers:

- A Performance tier with SSDs
- A Standard SAS tier with Enterprise SAS HDDs
- An Archive tier utilizing Midline SAS HDDs.

The MSA 2062 supports sub-LUN tiering and automated data movement between tiers. The MSA 2062 automated tiering engine moves data between available tiers based on the access characteristics of that data. Frequently accessed “pages” will migrate to the highest available tier delivering maximum I/O’s to the application.

Snapshot and Volume Copy

- All MSA 2062 arrays come standard with 512 snapshots.
 - Snapshots create up to 512 point-in-time copies of data.
 - Volume Copies create up to 128 point-in-time copies of data.
 - Volume copies become standard volumes when they are complete.
 - Recovery is instant - revert data from any previous Snapshot or Volume Copy.
 - Backup 'snapped' data to disk, virtual tape, or physical tape without a backup window.
 - If telephone support and software updates are desired for bundled software functionalities like 512 snapshots and volume copy software, a combination HW + SW support care pack must be purchased.
 - Hewlett Packard Enterprise does not provide warranty assistance for software products included with our base hardware products. Support is available with either the SupportPlus or SupportPlus24 Service options the hardware warranty component of these services is accounted for in the pricing of the SP and SP24 HPE Pointnext operational.
-

Remote Snap

All MSA 2062 arrays come standard with Remote Snaps. HPE MSA Remote Snap Software is array based functionality that provides remote replication on the HPE MSA 2062 array products. MSA Remote Snap is a form of asynchronous replication which consists of replication of block-level data from a volume on a local system to a volume on a second independent system. This second system may be co-located with the first system or may be located at a remote site.

- MSA Remote Snaps are used to determine the data to be replicated using the differences in snapshots on the primary volume, minimizing the amount of data to be transferred.
- MSA Remote Snap replication technology provides the ability to accomplish key data management and protection capabilities. First, because Remote Snap uses snapshots as the underlying technology can create multiple local recovery points which can be used for such tasks as to complement daily backups; second, replication provides the ability to access data in a remote site which could be used for dispersed operations; and third but definitely not least important replication allows for business continuance in the event of a failure on the primary site.
- In order to perform a replication, a snapshot of the volume to be replicated is taken, creating a point-in-time image of the data. This point-in-time image is compared to the point-in-time image taken during the previous replication and the changes are then replicated to the destination volume by copying the data represented by the snapshot via a transport medium such as TCP/IP (iSCSI) or Fibre Channel. The amount of data transferred is minimized through the use of snapshots whenever possible.
- Support of both Ethernet and Fibre Channel interconnects provides flexible options to the application environments.



Standard Features

- Snapshot based replication technology means only changed data will be replicated to alternate site
- Many to 1 replication (up to 4 nodes) - primary use case is to replicate from "many" branch offices to the home office for the purpose of backing up data from the branches.
- Advanced scheduler provides several options to IT administrators for business continuance
- Flexible architecture allows remote replication between MSA 2062 and MSA 2060 or MSA 1060 arrays using the virtual storage architecture and licensed for Remote Snap with the Advanced Data Services LTU.
- Snapshot based replication enables both local and remote recovery depending on the need. Snapshot replication isolates problems to a specific point in time which can be selected by the administrator. Additionally snapshot replication supports longer distance replication.
- Multiple relationships provide greater storage flexibility and utilization.
- Fast application recovery with minimal or no transaction loss
- Creation of disaster tolerant copies of your critical business data
- No-single-point-of-failure solution to increase the availability of your data
- With the improved disaster recovery features of the MSA 1060, MSA 2060 and MSA 2062, you can failover to the secondary / remote volume or volume group, map the secondary volume or volume group for access, then, when the primary array has recovered, failback to the primary volume or volume group, with the option to incorporate changes made to the secondary volume or volume group back to the primary volume or volume group.
- Another improvement in Remote Snap with the MSA 1060, MSA 2060 and MSA 2062 is the ability to reverse the direction of the replication set

Notes: One Advanced Data Services Suite License per array is required for replication. For example, if you have two MSA arrays performing replication (from Primary system to Remote System), you will need a total of 2 licenses.

HPE OneView for VMware vCenter

HPE OneView for VMware vCenter is a component within the HPE OneView plug-in for vCenter. It enables vSphere administrators to quickly obtain context-aware information and manage supported HPE storage devices like the MSA in their VMware vSphere environment directly from within vCenter. This plug-in operates independently of the core HPE OneView product and does not require a license to use. By providing a clear relationship between VM's, datastores and storage, the VMware administrator's productivity increases, as does the ability to ensure quality of service. Roles for administrators can be defined on an individual basis, providing the ability to apply specific permissions for both view and control functions.

HPE OneView for VMware vCenter supports mixed array environments including MSA Storage, and other HPE Storage systems including Primara Storage, 3PAR Storage, Nimble Storage, and StoreOnce.

When deployed with MSA Storage, HPE OneView provides the following:

- Active Management functionality for the MSA Storage:
 - Create/Expand/Delete a Datastore
 - Create a Virtual Machine from a template
- Monitors the health and status of the MSA Storage
- Displays LUN / volume connections from VMs and ESX servers to the arrays and provides the location and attributes of the MSA array within the SAN
- Identifies what storage features are available to allow administrators to match the features available on the MSA array to their requirements
- Provide a cluster-level view of the storage
- HPE OneView for VMware vCenter is downloadable from Software Depot:
<https://h20392.www2.hp.com/portal/swdepot/displayProductInfo.do?productNumber=HPVPR>



Standard Features

HPE OneView for System Center

HPE OneView for Microsoft System Center provides a comprehensive integration of HPE Storage, HPE Servers, HPE Blade System and HPE Virtual Connect with Microsoft System Center. HPE OneView for System Center enables management and monitoring of HPE MSA Storage running in Microsoft environment with a single pane-of-glass view to events/alerts, capacity and health dashboards and detailed virtual infrastructure information. It provides seamless integration with Microsoft System Center Operations Manager (SCOM) enabling predefined discovery and monitoring policies, event processing rules and topology views for HPE Storage including the MSA Storage Systems.

When deployed with the MSA 2062 array, HPE OneView for System Center provides the following:

- Monitors the health, events and alerts for the MSA 2062 – virtual pools, and volumes
- Provides topology information for VMs provisioned on the MSA Storage array

HPE OneView for System Center is downloadable at no charge from Software Depot:

https://h20392.www2.hpe.com/portal/swdepot/displayProductInfo.do?productNumber=System_Center

vStorage API for Array Integration (VAAI)

The vStorage API for Array Integration (VAAI) is one of the storage application programming interface (API) sets in vSphere. VAAI is an API storage partners can leverage to enhance performance of virtual machine (VM) management operations by delegating these operations to the storage array. With hardware offload, ESX/ESXi hosts perform certain operations faster and consume less server CPU and memory resources, and also storage port and storage fabric bandwidth. VAAI includes high performance and scalable VM data path primitives.

Storage Hardware Primitives for VAAI

- Full Copy or Hardware Assisted Move
 - Block Zeroing or Hardware Assisted Zeroing
 - Hardware Assisted Locking or Atomic Test and Set (ATS)
 - UNMAP reclaims space that is no longer on a thinly provisioned VMFS volume
-

LDAP Support

LDAP (Lightweight Directory Access Protocol) is an industry standard application protocol for accessing and maintaining distributed directory information services over an IP network. LDAP provides the ability to authenticate MSA users with a central directory.

- Domain or Directory Credentials are not stored on the MSA for authentication – avoids a security issue.
 - Once user groups are configured on all MSAs in your organization, users can be authenticated on any MSA through the Active Directory.
 - Uses an LDAP implementation to authenticate users with a Windows Active Directory.
 - The MSA CLI and SMU will allow the configuration of new LDAP users groups into the MSA security scheme (manage vs monitor users, interface restrictions Web/CLI/FTP).
 - Ability to authenticate Local or LDAP users.
-



Standard Features

I/O Workload Functionality

A beneficial user interface element called “I/O Workload” is included in the MSA web browser (SMU v4). The MSA array controllers keep track of a substantial amount of data pertaining to the I/O dynamics at a logical page level (4MB chunks). From this data, it is possible to provide some visibility to what percent of I/O's are being processed by what percent of the overall array's capacity across a 7 day timeline. While some workloads have “transient” data access patterns, many workloads have steady access patterns on small portions of the array's capacity. This produces “hot” pages in the array which remain hot a large amount of the array's uptime. Users would see substantial benefits if these pages could be served from the fastest media in the array (ideally SSDs). As has been described in the MSA's tiering functionality, the MSA array's tiering engine will work to position the hottest pages on the fastest media at any given time.

The new I/O Workload graph will show a line labeled Capacity and a line plot for each selected workload percentage (100%, 80%, or Other% value). Below are two examples of user scenarios where the I/O Workload Graph might be useful and how to utilize the data the graph provides.

- New User or SSD Installation.
- Once the MSA array is installed and has had workloads running against it for a week's time, the I/O Workload data will give a representation of what Capacity is servicing 100% of I/O and 80% of I/O. Users may select a custom % value if desired. In a new installation or in an installation with no SSD tier installed, the 80% line is a reasonable starting point for an SSD tier. Based on SSD RAID settings, customers can then calculate a good starting point with regard to SSD tier sizing based on that week's workload. While not a hard fast rule, it is a good starting point. These values should also be compared to the Best Practices “rule of thumb” which suggest that 5-15% of the array's capacity should be SSDs for tiered solutions.
- Users with existing SSD tiering or read caching installed and running.
- For arrays running with SSDs installed (tiered or read cache), the I/O Workload graph will have a dotted line which shows the installed SSD capacity. The I/O Workload graphs can be checked periodically to see where the 80% I/O line is with regard to the SSD capacity line. While there are no hard and fast rules which indicate good/bad situations, users can use the graph with other system performance tools to better understand specific dynamics of their installation and the normal dynamics of a system in the day-to-day activities for a specific environment.

Interpreting the I/O Workload graphs allow users to strike a balance between the SSD costs versus performance benefits. For example, some customers may be willing to have a couple of days where peak usage is far above the SSD capacity line as it may be acceptable to have slower performance as the system uses HDDs for a larger percentage of the workload I/O. This may be perfectly acceptable for systems sized to optimize \$/TB due to budget constraints. Other users may want to optimize the system such that a sizeable percentage of daily I/O have the opportunity to reside on SSD media (sized to 80% or 90%). When combined with other performance monitoring tools, the new I/O Workload function gives users some representation as to how the workloads and the MSA are working together in a user's real-world environment.

HPE Complete – Zerto

HPE MSA Storage users can leverage Zerto Virtual Replication to replicate applications and data from one MSA array to another MSA array. Popular use cases include departmental MSA storage replicated to enterprise storage, enterprise storage replicated into MSA array, or protect MSA workloads into the cloud.

Zerto operates on the hypervisor level and includes orchestration and automation built-in to enable faster recovery of workloads (RTO in minutes) at much lower Recovery Point Objective (RPO of seconds) available through other data protection tools like backup. Zerto is also a workload mobility tool and allow IT to confidently move workloads and data across heterogeneous storage or cloud.

Ordering, configuring and installing Zerto is simple. Zerto is licensed by number of Virtual Machines that are being protected or moved. For mobility use cases, order the appropriate number of migration licenses needed. For replication use cases, order the appropriate quantity of Zerto Virtual Replication licenses using a combination of the tiered licenses plus the corresponding maintenance part numbers. The license is independent of source and target array size, type or capacity being replicated. See the

Standard Features

HPE Complete/Zerto QuickSpecs for a complete list of part numbers. A corresponding MSA Advanced Data Services LTU is not required for data replication when using Zerto Virtual Replication. An MSA Advanced Data Services LTU would be required if deploying MSA array-based replication.

Zerto installs as a virtual machine under VMware or Hyper-V or in the Cloud as a VM in AWS and Azure in minutes Zerto does not install any components in the guest operating system and does not depend on any specific configuration of the storage or use MSA array or VMware snapshots to replicate and recover applications.

Zerto virtual replication is available on HPE Catalog via HPE Complete program.

For more information on the HPE Complete – Zerto solution, visit;

<https://h20195.www2.hpe.com/v2/getdocument.aspx?docname=a00006013enw>

HPE Complete – Arxscan

Arxscan is an HPE Complete Partner delivering innovative software that drives value through unique enterprise data center monitoring and reporting. Arxscan provides infrastructure monitoring for Storage, Network, Servers and Applications. Arxscan is fully supported on the HPE MSA 1060, 2060 and 2062 storage arrays, and is available for purchase directly from Hewlett Packard Enterprise. Arxscan's intuitive dashboard delivers an unprecedented view of how organizations store, distribute and protect their data, providing relevant views around device quality and performance metrics. Benefits include:

- Remote delivery from any location to any location worldwide.
- Supports all HPE arrays, OEM product lines, SAN switch and server OS platforms without agents.
- Quickly installed in under two hours in SMB, midrange or enterprise customer environments.
- Presents views that are business operations and infrastructure/system operations centric.
- Creates global collaborative touch points for all users of local and remote data center resources.
- One Stop Shop – ability to purchase complete solutions from HPE that include both HPE products and best-in-class third party branded products, all on a single HPE purchase order.

For more information please refer to **HPE Complete** on **HPE.com**

MSA Health Check Tool

MSA Health Check is a cloud-based tool that provides users insight into the general health of their MSA array. The tool uses a powerful rules-based analytics engine which can predict failures before they happen. The MSA Health Check tool performs a full sweep of analytics and checking thousands of data points from sensors inside the MSA array. The analytics engine will pick up common failure signatures and check against MSA best practices producing a simple, easy to digest PDF report with status and suggested courses of action to correct anything found in the scan. The tool is free of charge to HPE MSA customers. The MSA Health Check tool is supported across all current MSA 1060/2060/2062 arrays as well as the prior three generations of arrays (MSA P2000 G3, MSA 1040/2040/2042 and MSA 1050/2050/2052).

The tool is available immediately at: www.hpe.com/storage/MSAHealthCheck.

For more information on how to use HPE MSA Health Check, please review the **HPE MSA Health Check User Guide**.



Service and Support

Warranty

- MSA Storage Systems carry a 3 year limited warranty, parts only exchange, normal business hours, next business day response.
- MSA Enterprise SAS (15K and 10K RPM) SFF HDDs carry a 3 year limited warranty, parts only exchange, normal business hours, next business day response.
- MSA Midline SAS (7.2K RPM) LFF HDDs carry a 1 year limited warranty, parts only exchange, normal business hours, next business day response.
- MSA SSDs carry a 3 year limited warranty, parts only exchange, normal business hours, next business day response. MSA 2062 SSD warranty includes unconditional replacement in case of drive failure, media wear-out, or both.
- The MSA 2062 has been designed with customer self-repairable parts to minimize repair time and provide greater flexibility in performing defective parts replacement.

Please refer to Hewlett Packard Enterprise limited warranty Statement and parts replacement instructions for further details.

Service and Support

Protect your business beyond warranty with HPE Support Services

HPE Pointnext provides a comprehensive portfolio including Advisory and Transformational, Professional, and Operational Services to help accelerate your digital transformation. From the onset of your transformation journey, Advisory and Transformational Services focus on designing the transformation and creating a solution roadmap. Professional Services specializes in creative configurations with flawless and on-time implementation, and on-budget execution. Finally, operational services provides innovative new approaches like Flexible Capacity and Datacenter Care, to keep your business at peak performance. Hewlett Packard Enterprise is ready to bring together all the pieces of the puzzle for you, with an eye on the future, and make the complex simple.

Connect your devices

Unlock all of the benefits of your technology investment by connecting your products to Hewlett Packard Enterprise. Achieve up to 77% reduction in down time, near 100% diagnostic accuracy and a single consolidated view of your environment. By connecting, you will receive 24x7 monitoring, pre-failure alerts, automatic call logging, and automatic parts dispatch. HPE Proactive Care Service and HPE Datacenter Care Service customers will also benefit from proactive activities to help prevent issues and increase optimization. All of these benefits are already available to you with your server storage and networking products, securely connected to HPE support.

Learn more about getting connected at <http://www.hpe.com/services>

Optimized Care

HPE Proactive Care with 6 hour call-to-repair commitment, three year Support Service

HPE Proactive Care gives customers an enhanced call experience. When your products are connected to HPE, Proactive Care helps prevent problems and maintains IT stability by utilizing personalized proactive reports with recommendations and advice. This Service combines three years' proactive reporting and advice with our highest level of hardware support; the HPE 24x7, six hour hardware call-to-repair. Hewlett Packard Enterprise is the only leading manufacturer who makes this level of coverage available as a standard service offering for your most valuable servers and storage, including the HPE MSA Storage systems.

<https://www.hpe.com/h20195/v2/GetPDF.aspx/4AA3-8855ENW.pdf>



Service and Support

Standard Care

HPE Proactive Care with 24x7 coverage, three year Support Service

HPE Proactive Care gives customers an enhanced call experience. When your products are connected to HPE, Proactive Care helps prevent problems and maintains IT stability by utilizing personalized proactive reports with recommendations and advice. This Service combines three years proactive reporting and advice with our 24x7 coverage, four hour hardware response time when there is a problem.

<https://www.hpe.com/h20195/v2/GetPDF.aspx/4AA3-8855ENW.pdf>

Basic Care

HPE Foundation Care 24x7, three-year Support Service

HPE Foundation Care 24x7 gives you access to HPE 24 hours a day, seven days a week for assistance on resolving issues. This service includes need based Hardware onsite response within four hours. Simplify your support experience and make HPE your first call to help resolve hardware or software problems.

Foundation Care

HPE Foundation Care 24x7, three-year Support Service

HPE Foundation Care 24x7 gives you access to HPE 24 hours a day, seven days a week for assistance on resolving issues. This service includes need based Hardware onsite response within four hours. In addition, collaborative software support is included in this service that provides troubleshooting assistance on industry leading software running on your HPE server. Simplify your support experience and make HPE your first call to help resolve hardware or software problems.

<https://www.hpe.com/h20195/V2/GetDocument.aspx?docname=4AA4-8876ENW&cc=us&lc=en>

Related Services

HPE Hardware Installation

Provides for the basic hardware installation of HPE branded servers, HPE storage including the MSA 2062 devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

HPE Installation and Startup Service

Provides for the installation and startup of HPE technology including BladeSystems, C-Class enclosure, HPE ProLiant c-Class and Integrity server blades, storage blades, SAN switch blades, HPE Virtual Connect modules (Ethernet and Fibre Channel), Ethernet network interconnects, and InfiniBand, as well as the installation of one supported operating system type (Windows® or Linux).

HPE Datacenter Care service

Helps improve IT stability and security, increase the value of IT, and enable agility and innovation. It is a structured framework of repeatable, tested, and globally available services “building blocks.” You can deploy, operate, and evolve your datacenter wherever you are on your IT journey. With HPE Datacenter Care, you benefit from a personalized relationship with HPE via a single point of accountability for HPE and others’ products.

HPE Factory Express for Servers and Storage

HPE Factory Express offers configuration, customization, integration and deployment services for HPE servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed.

Factory Express offers service packages for simple configuration, racking, installation, complex configuration and design services as well as individual factory services, such as image loading, asset tagging, and custom packaging. HPE products supported through Factory Express include a wide array of servers and storage: HPE Integrity, HPE ProLiant, HPE Apollo, HPE ProLiant Server Blades,



Service and Support

HPE BladeSystem, as well as the HPE MSA Storage, HPE Primera Storage, HPE 3PAR Storage, HPE XP Storage, rackable tape libraries and configurable network switches.

HPE Education Services

Keep your IT staff trained making sure they have the right skills to deliver on your business outcomes. Book a class today and learn how to get the most from your technology investment. <http://www.hpe.com/ww/learn>

HPE Support Center

The HPE Support Center is a personalized online support portal with access to information, tools and experts to support HPE business products. Submit support cases online, chat with Hewlett Packard Enterprise experts, access support resources or collaborate with peers.

Learn more <http://www.hpe.com/support/hpesc>

HPE Insight Remote Support and HPE Support Center are available at no additional cost with a HPE warranty, HPE Support Service or HPE contractual support agreement.

For more information: <http://www.hpe.com/services>

Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.



Configuration Information

Step 1: MSA 2062 Base Configurations / Pre-Configured Systems

| Description | SKU |
|---|--------|
| MSA 2062 Storage Systems | |
| HPE MSA 2062 16Gb Fibre Channel LFF Storage | R0Q79A |
| HPE MSA 2062 16Gb Fibre Channel SFF Storage | R0Q80A |
| HPE MSA 2062 10GbE iSCSI LFF Storage | R0Q81A |
| HPE MSA 2062 10GbE iSCSI SFF Storage | R0Q82A |
| HPE MSA 2062 12Gb SAS LFF Storage | R0Q83A |
| HPE MSA 2062 12Gb SAS SFF Storage | R0Q84A |
| HPE MSA 2062 10GBASE-T iSCSI LFF Storage | R7J70A |
| HPE MSA 2062 10GBASE-T iSCSI SFF Storage | R7J71A |

Notes:

- Includes an SFF or LFF Array Chassis depending on model, two MSA 2060 controllers, two 1.92TB Read Intensive SSDs, one Advanced Data Services LTU (preinstalled on the array), two AC power supplies, two 1.5m PDU cords (IEC C14), one rack-mount kit.
- SFPs are not included in the base MSA 2062 Storage Systems.
- There are no converged protocol models with the MSA 2062 Storage Systems– you must select the appropriate Fibre Channel, iSCSI, or SAS array model.

Step 2: Select Your SFP+ Module

| | |
|---|--------|
| HPE MSA 16Gb Short Wave Fibre Channel SFP+ 4-pack Transceiver | C8R24B |
| HPE MSA 10Gb Short Range iSCSI SFP+ 4-pack Transceiver | C8R25B |

Notes:

- MSA 2062 Storage Systems do not ship with SFPs.
- Each MSA 2062 Storage Systems can be configured with either four or eight SFPs.
- MSA SFPs are for use with MSA 2062 FC or iSCSI Storage Systems.
- MSA 2062 SAS Storage Systems do not require SFP modules.
- Minimum of one SFP transceiver 4 pack is required for Fibre Channel models
- MSA 2062 10GbE iSCSI configurations can use Direct Attach Copper (DAC) cables instead of SFPs.
- iSCSI models require either an SFP 4 pack of transceivers (C8R25B only) or a DAC cable option.
- Controller host ports are recommended to be configured identically.
- Cannot mix FC transceivers with iSCSI transceivers in the same storage system.

Step 3: Select your Drives

- MSA Gen 6 HDDs and SSDs are for use with MSA Gen 6 Storage Systems only.
- MSA Gen 6 HDDs and SSDs are not compatible with prior generation MSA Storage Systems
- Prior Generation of MSA HDDs and SSDs are not compatible with MSA Gen 6 Storage Systems.
- Customers can mix SSD, Enterprise SAS, and SAS Midline (MDL) drives in the same array enclosure or drive enclosure.

SFF HDD 6-Pack Bundles

Select MSA SFF HDD options are available to purchase in bundles that include 6 drives. Purchasing MSA drives in bundles typically provides a lower purchase price than purchasing them individually. Check with your HPE sales representative or channel partner for further details.

| | |
|---|--------|
| HPE MSA 5.4TB SAS 12G Enterprise 15K SFF (2.5in) M2 3yr Wty 6-pack HDD Bundle | R0Q64A |
|---|--------|

Notes: Contains 6 x MSA 900GB 12G SAS 15K SFF Enterprise HDDs (R0Q53A)



Configuration Information

| Description | SKU |
|---|--------|
| HPE MSA 7.2TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty 6-pack HDD Bundle Notes: Contains 6 x MSA 1.2TB 12G SAS 10K SFF Enterprise HDDs (R0Q55A) | R0Q65A |
| HPE MSA 10.8TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty 6-pack HDD Bundle Notes: Contains 6 x MSA 1.8TB 12G SAS 10K SFF Enterprise HDDs (R0Q56A) | R0Q66A |
| HPE MSA 14.4TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty 6-pack HDD Bundle Notes: Contains 6 x MSA 2.4TB 12G SAS 10K SFF Enterprise HDDs (R0Q57A) | R0Q67A |
| LFF HDD 6-Pack Bundles | |
| Select MSA LFF HDD options are available to purchase in bundles that include 6 drives. Purchasing MSA drives in bundles typically provides a lower purchase price than purchasing them individually. Check with your HPE sales representative or channel partner for further details. | |
| HPE MSA 48TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle Notes: Contains 6 x MSA 8TB 12G SAS 7.2K LFF Midline HDDs (R0Q59A) | R0Q69A |
| HPE MSA 60TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle Notes: Contains 6 x MSA 10TB 12G SAS 7.2K LFF Midline HDDs (R0Q60A) | R0Q70A |
| HPE MSA 72TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle Notes: Contains 6 x MSA 12TB 12G SAS 7.2K LFF Midline HDDs (R0Q61A) | R0Q71A |
| HPE MSA 84TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle Notes: Contains 6 x MSA 14TB 12G SAS 7.2K LFF Midline HDDs (R0Q62A) | R0Q72A |
| HPE MSA 96TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle Notes: Contains 6 x MSA 16TB 12G SAS 7.2K LFF Midline HDDs (R3U72A) | R3U73A |
| HPE MSA 108TB SAS 12G Midline 7.2K LFF M2 1-year Warranty 6-pack HDD Bundle Notes: Contains 6 x MSA 18TB 12G SAS 7.2K LFF Midline HDDs (R7L70A) | R7L71A |
| SFF HDDs | |
| HPE MSA 900GB SAS 12G Enterprise 15K SFF (2.5in) M2 3yr Wty HDD | R0Q53A |
| HPE MSA 600GB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty HDD | R0Q54A |
| HPE MSA 1.2TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty HDD | R0Q55A |
| HPE MSA 1.8TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty HDD | R0Q56A |
| HPE MSA 2.4TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty HDD | R0Q57A |
| LFF HDDs | |
| HPE MSA 6TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R0Q58A |
| HPE MSA 8TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R0Q59A |
| HPE MSA 10TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R0Q60A |
| HPE MSA 12TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R0Q61A |
| HPE MSA 14TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R0Q62A |
| HPE MSA 16TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R3U72A |
| HPE MSA 18TB SAS 12G Midline 7.2K LFF M2 1-year Warranty HDD | R7L70A |

Configuration Information

| Description | SKU |
|--|--------|
| SFF SSDs | |
| HPE MSA 960GB SAS 12G Read Intensive SFF (2.5in) M2 3yr Wty SSD | ROQ46A |
| HPE MSA 1.92TB SAS 12G Read Intensive SFF (2.5in) M2 3yr Wty SSD | ROQ47A |
| HPE MSA 3.84TB SAS 12G Read Intensive SFF (2.5in) M2 3yr Wty SSD | R3R30A |
| LFF SSDs | |
| HPE MSA 1.92TB SAS 12G Read Intensive LFF (3.5in) M2 3yr Wty SSD | ROQ49A |

Step 4: Options

Drive Enclosures

| | |
|---|--------|
| HPE MSA 2060 SAS 12G 2U 12-disk LFF Drive Enclosure | ROQ39A |
| HPE MSA 2060 SAS 12G 2U 24-disk SFF Drive Enclosure | ROQ40A |

Notes:

- Each drive enclosure includes a single rack-mount kit and two 0.5m MiniSAS HD to MiniSAS HD cables.
- Add up to nine additional drive enclosures.
- MSA 2060 LFF Drive Enclosures can be connected to either the MSA 2062 SFF or LFF Storage systems.
- MSA 2060 SFF Drive Enclosures can be connected to either the MSA 2062 SFF or LFF Storage systems

Drive Enclosure Cables

| | |
|--|------------|
| HPE External 1.0m (3ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable | 716195-B21 |
| HPE External 2.0m (6ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable | 716197-B21 |

Notes: When connecting a MSA 2062 controller to a drive enclosure if a longer cable is needed.

Security Option

| | |
|--------------------|------------|
| HPE Bezel Lock Kit | 875519-B21 |
|--------------------|------------|

DC Power Option

| | |
|--|--------|
| HPE MSA 2060 764W -48VDC Hot Plug Power Supply Kit | ROQ90A |
|--|--------|

Notes:

- All MSA 2062 array enclosures and drive enclosures come standard with 2 AC power supplies.
- If DC power is desired, then two DC power supplies must be selected on the array enclosure and all drive enclosures.
- DC Power Supplies can be ordered with factory integration or with field integration. With factory integrated orders, the AC power supplies will not be shipped.
- One (1) 48VDC 2.3M power cord is included with each ROQ90A kit.

Power Cords

| | |
|--|--------|
| HPE C13 - C14 WW 250V 10Amp 2.0m Jumper Cord | A0K02A |
| HPE C13 - C14 WW 250V 10A Gray 0.7m Jumper Cord | A0K03A |
| HPE C13-NEMA 6-15P 10A/250V 3.6m Black Power Cord | AON33A |
| HPE C13 - Nema 5-15P US/CA 110V 10Amp 1.83m Power Cord | AF556A |
| HPE C13 - GB-1002 CN 250V 10Amp 1.83m Power Cord | AF557A |
| HPE C13 - IRAM -2073 AR 250V 10A 2.5m Power Cord | AF558A |
| HPE C13 - KSC- 8305 KR 250V 10Amp 1.83m Power Cord | AF560A |



Configuration Information

| Description | SKU |
|---|--------|
| HPE C13 - CNS-690 TW 110V 13Amp 1.83m Power Cord | AF561A |
| HPE C13 - IS-1293 IN 240V 6Amp LV 2.0m Power Cord | AF562A |
| HPE C13 - SI-32 IL 250V 10Amp 1.83m Power Cord | AF564A |
| HPE C13 - SEV 1011 CH 250V 10Amp 1.83m Power Cord | AF565A |
| HPE C13 - DK-2.5A DK 250V 10Amp 1.83m Power Cord | AF566A |
| HPE C13 - SABS-164 ZA 250V 10Amp 2.5m Power Cord | AF567A |
| HPE C13 - CEE-VII EU 250V 10Amp 1.83m Power Cord | AF568A |
| HPE C13 - AS3112-3 AU 250V 10Amp 2.5m Power Cord | AF569A |
| HPE C13 - BS-1363A UK/HK/SG 250V 10Amp 1.83m Power Cord | AF570A |
| HPE C13 - JIS C8303 JP 100V 12Amp 2.0m Power Cord | AF572A |
| HPE C13 - C14 WW 250V 10Amp Flint Gray 2.0m Jumper Cord | AF573A |
| HPE C13 - NBR-14136 BR 250V 10Amp 1.83m Power Cord | AF591A |
| HPE C13-C14 IN 250V 10Amp 2m Black Jumper Cord | R1C65A |

Notes:

- Two PDU cables: one 142263-008 (Black) and one 1422633-013 (Grey), ship standard with all AC-powered enclosures
- The power cords may be used by customers that desire to plug their base array and/or drive enclosures into a wall outlet or PDU.

Step 5: Choose cables for Host Connection

Fibre Channel Infrastructure

PremierFLexOM4 type cables

| | |
|---|--------|
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 1m Cable | QK732A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 2m Cable | QK733A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 5m Cable | QK734A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 15m Cable | QK735A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 30m Cable | QK736A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 50m Cable | QK737A |

OM3 Fibre FC to LC cables

| | |
|--|--------|
| HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable | AJ833A |
| HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable | AJ834A |
| HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable | AJ835A |
| HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable | AJ836A |
| HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable | AJ837A |
| HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable | AJ838A |
| HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable | AJ839A |



Configuration Information

| Description | SKU |
|---|------------|
| 10GbE Infrastructure | |
| Direct Attach Copper Cables | |
| Aruba 10G SFP+ to SFP+ 1m Direct Attach Copper Cable | J9281D |
| Aruba 10G SFP+ to SFP+ 3m Direct Attach Copper Cable | J9283D |
| Aruba 10G SFP+ to SFP+ 7m Direct Attach Copper Cable | J9285D |
| HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 3m Direct Attach Copper Cable | 487655-B21 |
| HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 5m Direct Attach Copper Cable | 537963-B21 |
| HPE FlexNetwork X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable | JD095C |
| HPE FlexNetwork X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable | JD096C |
| HPE FlexNetwork X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable | JD097C |
| HPE FlexNetwork X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable | JG081C |
| HPE FlexNetwork X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable | JC784C |
| HPE FlexNetwork X240 40G QSFP+ to 4x10G SFP+ 1m Direct Attach Copper Splitter Cable | JG329A |
| HPE FlexNetwork X240 40G QSFP+ to 4x10G SFP+ 3m Direct Attach Copper Splitter Cable | JG330A |
| HPE FlexNetwork X240 40G QSFP+ to 4x10G SFP+ 5m Direct Attach Copper Splitter Cable | JG331A |
| SAS Infrastructure | |
| Mini SAS HD to Mini SAS Cables | |
| HPE 1.0m External Mini SAS High Density to Mini SAS Cable | 716189-B21 |
| HPE 2.0m External Mini SAS High Density to Mini SAS Cable | 716191-B21 |
| HPE 4.0m External Mini SAS High Density to Mini SAS Cable | 716193-B21 |
| Mini SAS HD to Mini SAS HD Cables | |
| HPE External 1.0m (3ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable | 716195-B21 |
| HPE External 2.0m (6ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable | 716197-B21 |
| HPE External 4.0m (13ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable | 716199-B21 |

Notes:

- These cables are used to connect the c-Class 6Gb BladeSystem SAS switch to MSA 2060 SAS Storage system.
- These are not used for connecting the MSA 1060 to a drive enclosure.

Notes:

- These cables are used to connect the DL and ML ProLiant 12Gb SAS Servers to MSA 2060 SAS Storage system.
- The 1.0m and 2.0m Mini-SAS HD to Mini-SAS HD cables can also be used for connecting a MSA 2060 SAS controller to a SFF or LFF drive enclosure.

Step 6: Software

- The MSA Advanced Data Services LTU comes standard on the MSA 2062 models.
- Visit HPE Complete on HPE.com for information on Zerto Virtual Replication and Arxscan Arxview software that is supported on the MSA 1060/2060/2062 Storage.



Technical Specifications

MSA 2062

Power requirements

| | |
|--|--|
| Input Power Requirements (typical-running I/O) SFF/LFF arrays | 120VAC 3.07A, 293-361 W; 220VAC 1.58A, 289-352W |
| Max Input Power | 100-240 VAC, 50/60 Hz., 4.38-2.17A; 48-60 VDC 10.4A/8.3A |
| Heat Dissipation | 1766 BTU/hr |

Temperature and Humidity RangesPhysical

| | |
|------------------------|---|
| Operating Temperature | ASHRAE A3 5°C to 40°C, -12°C DP & 8 to 24°C DP (Derate maximum allowable dry-bulb temperature 1°C/175m above 900m) |
| Shipping Temperature | -40°F to 158°F (-40°C to 70°C) |
| Operating Humidity | Up to 85% RH |
| Non-Operating Humidity | Up to 90% RH @ 30°C |

Physical

| | |
|--|-------------------|
| Height | 3.5 in (8.9 cm) |
| Depth (Back of chassis ear to controller latch) | 20.0 in (50.8 cm) |
| Depth (Front of chassis ear to back of cable bend) | 26.4 in (66.9 cm) |
| Width (Chassis only) | 17.5 in (44.5 cm) |
| Width (Chassis with bezel ear caps) | 19.0 in (48.3 cm) |

Weight LFF Enclosure

| | |
|--|---------------|
| Chassis empty | 11 lb (5 kg) |
| Controller enclosure (fully populated with FRUs and disks) | 71 lb (32 kg) |
| Expansion enclosure (fully populated with FRUs and disks) | 62 lb (28 kg) |

Weight SFF Enclosure

| | |
|--|---------------|
| Chassis empty | 11 lb (5 kg) |
| Expansion enclosure (fully populated with FRUs and disks) | 66 lb (30 kg) |
| Controller enclosure (fully populated with FRUs and disks) | 55 lb (25 kg) |

Acoustic Ratings

| | |
|----------------|--|
| Sound Power | A weighted sound power LWAd - 8.3 B |
| Sound Pressure | A weighted sound pressure LpAm - 74dBA |

Shock and Vibration

| | |
|----------------------------|--|
| Shock, Operational | 5G, 11 ms |
| Shock, Non-Operational | 15G, 10ms |
| Vibration, Operational | 5-500Hz, 0.18 Grms |
| Vibration, Non-Operational | x-axis (5-300Hz) 0.8 Grms z-axis (5-300Hz) 1.2 Grms |



Technical Specifications

Power Supply Details

2U Flex 580W PSU 80+ Gold

| | | | |
|--|----------|----------|----------|
| Input Voltage Range (V rms) | 100-240 | | |
| Frequency Range (Hz) | 50-60 | | |
| Nominal Input Voltage | 115 | 208 | 230 |
| Maximum Output Wattage Rating (W) | 584 | 584 | 584 |
| Nominal Input Current (Arms) | 5.7 | 3.2 | 2.8 |
| Maximum Input Wattage Rating (W) | 652 | 645 | 644 |
| Maximum Rated VA (VA) | 653 | 661 | 650 |
| Efficiency (%/100) | 0.896 | 0.905 | 0.907 |
| Power Factor | 0.999 | 0.976 | 0.991 |
| Leakage Current (mA) | <0.8 | | |
| Maximum Inrush Current (A peak) | 45 | | |
| Maximum Inrush Current Duration (ms) | 40 | | |
| Maximum British Thermal Unit Rating (BTU-hr) | 2224.233 | 2201.382 | 2196.286 |

MSA 2062 Regulatory Information

| | |
|--------------------------------------|--|
| Safety | <ul style="list-style-type: none"> UL/CSA 62368-1 (USA/Canada) EN 62368-1 (European Union) IEC 60950-1 (International) |
| Power | <ul style="list-style-type: none"> EU Regulation 2019/424 (Lot 9) |
| Electromagnetic Compatibility | <ul style="list-style-type: none"> VCCI Class A (Japan) FCC Class A (USA) ICES-003 Class A (Canada) EN55032 : (European Union Class A); CISPR 32 (International Class A) EN61000-3-2 : (Harmonics) (European Union) EN61000-3-3 : (Flicker) (European Union) EN 55024 (European Union, Immunity, Class A); CISPR 24 (International Immunity, Class A) AS/NZS CISPR 32, Class A (Australia, New Zealand) CNS 13438 Taiwan, Class A (Taiwan) KN32 Class A (Emissions Class A); KN35 (Immunity) (S Korea) |
| RoHS and WEEE | <ul style="list-style-type: none"> RoHS-6/6 China RoHS WEEE |
| Country Approvals | United States, Australia/New Zealand, Canada, European Union, Japan, South Korea, Taiwan |



Technical Specifications

MSA 2062 Benchmark Performance Results

The performance figures provided here are for reference as many variables exist between array configurations, workloads, drive types, disk group setup parameters and host system setup.

Hewlett Packard Enterprise has traditionally published a set of end-to-end MSA performance specifications that are fed into HPE Sizer tools which are based on conservative real-world configurations. For consistency, the MSA performance numbers have been documented in both Benchmark and End-to-End Performance tables. These numbers are subject to change without notice.

HPE MSA 2062 Benchmark Performance Results

| Benchmark Performance Results ¹ | HPE MSA 2062 (with SSDs) |
|--|--------------------------|
| IOPS | |
| Random Reads ² | 325,000 |
| Random Writes ³ | 175,000 |
| Sequential⁴ | |
| Segmented Sequential Reads ⁵ | 13.1 GB/s |
| Segmented Sequential Writes ⁶ | 7.3 GB/s |

Notes:

- ¹Performance results were generated using internal HPE test tools. Number and type of applications, drive type and number of drives, operating system used, and the number of hosts will affect overall performance. This table is provided strictly as a test-lab comparison.
- ²Dual controller configuration, four SSDs, RAID 1, two SSDs per disk group; one disk groups per pool, four volumes per pool, block size: 8k, 16Gb FC direct connect to array.
- ³Dual controller configuration, 20 SSDs, RAID 10, ten SSDs per disk group; one disk groups per pool, four volumes per pool, block size: 8k, 16Gb FC direct connect to array.
- ⁴Sequential performance numbers were generated using segmented sequential workloads. For segmented sequential workloads with a queue depth greater than 1, each sequential stream is targeted to operate on a separate LBA range. Other types of sequential workloads that target specific LBA ranges may achieve higher results
- ⁵Dual controller configuration, 20 SSDs, RAID 10, ten SSDs per disk group, one disk group per pool, four volumes per pool, 256k block size, 16Gb FC direct connect to array.
- ⁶Dual controller configuration, 18 SSDs, RAID 5, nine SSDs per disk group, one disk group per pool, four volumes per pool, 256k block size, 16Gb FC direct connect to array.



Technical Specifications

MSA 2062 End-to-End Performance Figures

| Storage Model | MSA 2062 FC | | MSA 2062 iSCSI | | MSA 2062 SAS | |
|--|----------------------|---------|--------------------------|---------|-----------------------|---------|
| Host Protocol | 16Gb FC ² | | 10GbE iSCSI ² | | 12Gb SAS ² | |
| Drive Technology | HDD | SSD | HDD | SSD | HDD | SSD |
| MSA 2062 RAID1 / RAID 10 Performance Results ^{3,4,5,6,7} | | | | | | |
| Random Reads IOPs | 49,900 | 300,900 | 43,400 | 221,100 | 49,900 | 294,200 |
| Random Writes IOPs | 31,600 | 161,800 | 31,600 | 132,600 | 31,700 | 160,800 |
| Random Mix 60/40 IOPs | 40,100 | 226,300 | 39,800 | 175,100 | 40,100 | 223,900 |
| Sequential Reads MB/s ¹ | 8,400 | 12,100 | 5,500 | 7,700 | 8,400 | 12,100 |
| Sequential Writes MB/s ¹ | 4,000 | 5,300 | 3,700 | 4,400 | 4,000 | 5,300 |
| MSA 2062 RAID 5 Performance Results ^{8,9,10,11} | | | | | | |
| Random Reads IOPs | 48,100 | 275,400 | 41,300 | 211,100 | 48,000 | 269,500 |
| Random Writes IOPs | 15,500 | 60,500 | 15,600 | 55,000 | 15,600 | 60,500 |
| Random Mix 60/40 IOPs | 27,300 | 112,500 | 27,200 | 98,000 | 27,100 | 112,500 |
| Sequential Reads MB/s ¹ | 8,000 | 11,800 | 5,400 | 7,700 | 8,000 | 11,800 |
| Sequential Writes MB/s ¹ | 5,800 | 6,700 | 4,500 | 4,500 | 5,800 | 6,700 |
| MSA 2062 RAID 6 Performance Results ^{12,13,14,15} | | | | | | |
| Random Reads IOPs | 48,900 | 273,000 | 42,000 | 210,200 | 48,800 | 266,100 |
| Random Writes IOPs | 12,000 | 52,200 | 12,000 | 47,000 | 12,000 | 52,000 |
| Random Mix 60/40 IOPs | 20,300 | 101,800 | 20,300 | 89,100 | 20,300 | 101,300 |
| Sequential Reads MB/s ¹ | 8,000 | 12,100 | 5,500 | 7,800 | 8,000 | 12,100 |
| Sequential Writes MB/s ¹ | 5,700 | 6,300 | 4,300 | 4,400 | 5,700 | 6,300 |
| MSA 2062 MSA-DP+ Performance Results ^{16,17,18} | | | | | | |
| Random Reads IOPs | 48,600 | 267,600 | 41,800 | 207,700 | 48,600 | 262,000 |
| Random Writes IOPs | 11,700 | 52,300 | 11,800 | 47,400 | 11,800 | 52,400 |
| Random Mix 60/40 IOPs ¹ | 20,300 | 101,900 | 20,300 | 89,200 | 20,300 | 101,200 |
| Sequential Reads MB/s ¹ | 8,000 | 12,100 | 5,400 | 7,800 | 8,000 | 12,100 |
| Sequential Writes MB/s ¹ | 5,400 | 6,300 | 4,300 | 4,400 | 5,400 | 6,300 |

Notes:

- Number and type of applications, drive type and number of drives, operating system used, and the number of hosts will affect overall performance. This table is provided strictly as a test-lab comparison. These numbers reflect a full array configuration with the maximum number of front-end ports and controllers. The test results shown for the HPE MSA 2062 are designed to give a conservative reference point for comparisons.
- All performance numbers were captured using dual controller configurations.
- All performance numbers were captured using four volumes per pool.
 - o ¹Sequential tests (MB/s) are based on 256K block sizes and random tests (IOPS) are based on 8K block sizes. For sequential workloads with a queue depth greater than 1, each sequential stream is targeted to operate on a separate LBA range. Other types of sequential workloads that target specific LBA ranges may achieve higher results. Results cannot be expected with a single host.
 - o ²Fibre Channel results were measured using 16 Gb FC Host Bus Adapters. SAS results were measured using 12 Gb SAS Host Bus Adapters. 10 GbE iSCSI results were measured using 10GbE iSCSI Host Bus Adapters. Hosts were directly attached to the HPE MSA 2060 array.
 - o ³RAID 1 Solid State Drive random read and mixed results: 4 SSDs, 2 SSDs per disk group, 1 disk group per pool.
 - o ⁴RAID 10 Solid State Drive random write results: 8 SSDs, 4 SSDs per disk group, 1 disk group per pool.
 - o ⁵RAID 10 Solid State Drive sequential results: 20 SSDs, 10 SSDs per disk group, 1 disk group per pool.
 - o ⁶RAID 10 Hard Disk Drive sequential results: 96 10K HDDs, 12 drives per disk group, 4 disk groups per pool.
 - o ⁷RAID 10 Hard Disk Drive random results: 240 10K HDD, 10 drives per disk group, 12 disk groups per pool.

Technical Specifications

- o ⁸RAID 5 Solid State Drive random results: 6 SSDs, 3 SSDs per disk group, 1 disk group per pool.
- o ⁹RAID 5 Solid State Drive sequential results: 18 SSDs, 9 SSDs per disk group, 1 disk group per pool.
- o ¹⁰RAID 5 Hard Disk Drive sequential results: 90 10K HDD, 9 drives per disk group, 5 disk groups per pool.
- o ¹¹RAID 5 Hard Disk Drive random results: 234 10K HDD, 9 drives per disk group, 13 disk groups per pool.
- o ¹²RAID 6 Solid State Drive random results: 8 SSDs, 4 SSDs per disk group, 1 disk group per pool.
- o ¹³RAID 6 Solid State Drive sequential results: 20 SSDs, 10 SSDs per disk group, 1 disk group per pool.
- o ¹⁴RAID 6 Hard Disk Drive sequential results: 80 10K HDD, 10 drives per disk group, 4 disk groups per pool.
- o ¹⁵RAID 6 Hard Disk Drive random results: 240 10K HDD, 10 drives per disk group, 12 disk groups per pool.
- o ¹⁶MSA-DP+ Solid State Drive results: 24 SSDs, 12 SSDs per disk group, 1 disk group per pool.
- o ¹⁷MSA-DP+ Hard Disk Drive sequential results: 96 10K HDD, 12 drives per disk group, 4 disk groups per pool.
- o ¹⁸MSA-DP+ Hard Disk Drive random results: 240 10K HDD, 30 drives per disk group, 4 disk groups per pool.

Environment-friendly Products and Approach End-of-life Management and Recycling

Hewlett Packard Enterprise offers **end-of-life product return, trade-in, and recycling programs**, in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard Enterprise web site. These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.



Summary of Changes

| Date | Version History | Action | Description of Change |
|-------------|-----------------|---------|---|
| 06-Jul-2021 | Version 5 | Changed | Added 10GBase-T models and other updates. |
| 06-Apr-2021 | Version 4 | Changed | Added 18TB HDD option, updated OS support, updated temperature and humidity specifications |
| 18-Jan-2021 | Version 3 | Changed | Added power supply details, temperature and humidity ranges, system certifications, and other textual updates |
| 16-Nov-2020 | Version 2 | Changed | Updated content on SFPs, added Acoustic/Shock/Vibe specifications, and updated HDD and SSD content. |
| 08-Sep-2020 | Version 1 | New | New QuickSpecs. |



Copyright

Make the right purchase decision.

Contact our presales
specialists.



Chat



Email



Call



Get updates

© Copyright 2021 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Intel® and Xeon® are registered trademarks of Intel Corporation in the U.S. and other countries. Microsoft®, Windows®, and Windows Server® are U.S. registered trademarks of the Microsoft group of companies.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less

a00094630enw - 16616 - Worldwide - V5 - 06-July-2021



Hewlett Packard
Enterprise