


- 9 blade design with enhanced air pressure technology
- Dual-Ring setup for perfect illumination inside and out
- 32 addressable LEDs offering complex RGB effects
- 4-PIN PWM fan-speed control and 3-PIN +5V A-RGB M/B Sync supported

CHIEFTRONIC's NOVA A-RGB fan set comes with beautiful illumination from a dual-ring design to ensure smooth and full lighting with 16 LEDs on the inner ring as well as 16 more LEDs on the outer ring. Additional frame design elements on the outer ring give the Nova fans a distinct visual that impresses.



Fan speeds can be controlled either via the control hub or via M/B PWM fan ports to ensure the optimal balance between cooling performance and silent operations.











Technical data	
Model	NF-3012-RGB
Connectors	Fan: 4 pin PWM ; ARGB: 3 pin
Dimension	120 mm x 120 mm x 25 mm (each)
Bearing Type	Hydraulic
LED Type	Addressable RGB (A-RGB)
LED Count	32 pcs (Inner Ring: 16 pcs ; Outer Ring: 16pcs)
Rated Voltage	FAN: DC12V; LED: DC5V
Rated Current	0.29A (Max: 0.65A)
Operating Voltage	7V -13.2V
Fan Speed (RPM)	1600 RPM ± 10%
Air Flow (CFM)	68 CFM
Air Pressure (mmH2O)	2.2 mmH2O
Noise Level (dBA)	24 dBA (Max: 28)
Scope of delivery	3x 120mm A-RGB Dual Ring Rainbow fan, 1x Control Hub DF-100 (5x 4PIN PWM fan ports, 6x +5V A-RGB LED ports),
	1x Remote Control, 1x +5V A-RGB and PWM M/B sync cable ,1x SATA power cable, 12x Mounting screws
RGB Sync Compatibilities	ASUS™ AURA SYNC, MSI™ MYSTIC LIGHT SYNC, ASROCK™ POLYCHROME SYNC, GIGABYTE™ RGB FUSION
Warrenty	24 Months
	Varsion : 08/2021

Version: 08/2021

^{*} The listed specifications may be altered at any point in time without any pre-notice.

^{**} CHIEFTRONIC® is a registered trade mark. All other brands and/or logos are property of the respective owners.