

E1-Zoom-IP-Camera-Specifications

E1-Zoom-IP-Camera-Specifications		
Hardware Features	Model	E1 Zoom
	Image Sensor	1/2.7" CMOS Sensor
	Display Resolution	2560x1920 (5 Megapixels)
	Lens	f=2.8-8mm Autofocus, F=1.6, with IR Cut
	Zoom	3X Optical Zoom
	Angle of View	Horizontal: 48° - 98° Vertical: 37° - 75°
	Pan/Tilt Angle	Horizontal: 355° Vertical: 50°
	Minimum Illumination	0 Lux (with IR Illuminator)
	IR Distance	12 Meters (40ft) (LED: 10pcs/14mil/850nm)
	Dimension	Ø80x111mm
	Weight	250g
	Power Input	DC 5.0V/1A
	Interface	Power Interface Micro SD Card Slot Built-in Microphone and Speaker Reset Button
	Software Features	Protocols & Standards
Image Compression		H.264
Maximal Frame Rate		20fps
Code Rate		1024Kbps ~ 4096Kbps (Default: 4096Kbps)
Audio		Two-Way Audio
Maximal User Access		20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Browser Supported		IE, Edge, Chrome, Firefox, Safari
OS Supported		PC: Windows, Mac OS; Smartphone: iOS, Android
Record Mode		Motion Recording
Alarm		Siren; Customized Voice-Recordable Alerts
Works with		Google Assistant; Reolink Cloud *available in some countries
Wireless Features	Wireless Standard	IEEE 802.11a/b/g/n
	Operating Frequency	2.4/5 GHz
	Wireless Security	WPA-PSK/WPA2-PSK
Other Parameters	Temperature	Operating Temperature: -10°C~+55°C Storage Temperature: -40°C~70°C
	Humidity	Operating Humidity: 20% ~ 85% Storage Humidity: 10% ~ 90%
	Waterproof	No