

Reolink-Duo-PoE-IP-Camera-Specifications			
	Model	Reolink Duo PoE	
Video & Audio	Image Sensor	1/3" CMOS Sensors	
	Video Resolution	Default: 2560X1440 (4.0 Megapixels) at 22 frames/sec	
	Lens	f = 4.0 mm fixed, F = 2.0	
	Video Format	H.264	
	Field of View	Horizontal:	150°
		Vertical:	44°
	Day & Night	Auto-switching with IR cut filter	
	Infrared Night Vision	30 Meters (LED: 6pcs/20mil/850nm)	
	Color Night Vision	Spotlight: 8pcs/5W/6500K/560 Lumens	
Audio	Two-way audio		
Power	POE	IEEE 802.3af, 48V Active	
	DC Power	DC 12V~2A, <12W	
Interface	Power	DC power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps; RJ45	
	Storage	Micro SD card slot (Max. 256GB)	
	Audio	Built-in microphone and speaker	
Software Features	Frame Rate	Mainstream: 2fps - 25fps (default: 22fps)	
		Substream: 4fps - 15fps (default: 10fps)	
	Code Rate	Mainstream: 1024Kbps - 5120Kbps (default: 4096Kbps)	
		Substream: 64Kbps - 512Kbps (default: 256Kbps)	
	Browser Supported	IE, Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Smart Alarm	Motion detection/person detection/vehicle detection	
	Record Mode	Motion-triggered recording (default); scheduled recording; 24/7 recording	
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P		
Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)		
Working Environment	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)	
	Humidity	Operating humidity: 10% ~ 90%	
	Waterproof	IP66	
Size & Weight	Dimension	195x103x56 mm	
	Weight	650g	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/	